

VINYLSPORT M EVERLAY 8,75 MM



Vinyl flooring for indoor sport use, supplied in rolls of 180 cm width, with a constant total thickness of at least 7 mm, composed of:

- a surface layer of 2 mm thickness, tested according to ISO 24340, consisting of an embossed wear layer of 0,8 mm, provided with solid color or wood effect, and a high density fiberglass-reinforced layer of 1,2 mm, which ensures high dimensional stability (0,1% according to UNI EN ISO 23999) and excellent wear resistance (≤ 100 mg according to UNI EN ISO 5470-1);
- an expanded dual-density vinyl foam layer with anti-slip backing for a better comfort and safety;
- a factory-applied surface protective coating which ensures constant and uniform friction, enhanced durability, high antibacterial properties, and easier maintenance.

This product is ideal for a multisport indoor hall where different indoor sport competitions are held, such as basketball, handball, volleyball, badminton or futsal.

The flooring contains at least 30% of raw materials classified as recycled, recovered or as by-products.

The floor is paired on-site with a 1,2 mm thick underlayment supplied in rolls. The underlayment, made of fiberglass and treated on both sides with synthetic elastomeric resins, is dimensionally stable, moisture resistant and provides insulating properties. The underside in contact with the ground is lightly textured with small embossed stems that improve the overall stability of the flooring system. This product has been certified to be in compliance with European Standards EN 13984 ("Flexible sheets for waterproofing") including Declaration Of Performance (DoP, CE marking).

The two layers are coupled together, using an appropriate adhesive, to provide a loose laid system with a **uniform thickness of 8,75 mm.**

The combination of the underlayment guarantees the stability of the system while providing complete protection against high humidity rates coming from subfloor, which significantly extends the product life.

STANDARDS

This product has been certified to be in compliance with the European Standard EN 14904 ("Surfaces for sports areas - Multi-sports floor systems for indoor use", Shock absorption ≥ 25 , Class P1) including Declaration Of Performance (DoP, CE marking) and it is rated Euroclass Cfl-S1 in accordance with the EN 13501.

This product has been certified in compliance with the following schemes and standards for Indoor Air Quality programs (VOC, Volatile Organic Compounds emissions):

- French scope (2011-321): Class A+.
- Italian regulation CAM (Minimum Environmental Criteria) following D.M. 06/23/2022.
- M1 - Emission Class for Building Material (RTS, Finland).

The surface has excellent natural antibacterial characteristics, without the addition of biocidal ingredients inside the product: in tests carried out according to ISO 22196, the killing of inoculated bacteria exceeds 99,9999% in 24 hours, with an antimicrobial activity factor "R" greater than 6.

This product has been rated "Non Hazardous" by external laboratory in accordance with the European Waste Catalogue. This means that it does not present a subrisk to public health or cause adverse effects on the environment.



This product complies with the applicable requirements of REACH (Registration, Evaluation, Authorisation and Restriction of Chemicals) Regulation (CE 1907/2006), including SVHC (Substances of Very High Concern) obligations and Annex XVII restrictions, including PAHs (Polycyclic Aromatic Hydrocarbons), as well as Regulation (EU) 2019/1021 on Persistent Organic Pollutants (POPs). The product is not intentionally formulated with PFAS (Per- and Polyfluoroalkyl Substances).

Furthermore, where applicable, it meets the requirements of the Italian Minimum Environmental Criteria (CAM) concerning recycled content, volatile organic compound (VOC) emissions, and the absence of restricted or hazardous flame retardants.

This product is designed and manufactured according to UNI EN ISO 9001 certification.

CERTIFICATIONS

Available International Sport Federation certificates for this product:

FIBA Certificate of Approval for Synthetic Flooring Category, Competition Level 2

BWF Synthetic Flooring Certificate


IHF Certificate of Approval for Synthetic Floorings

IFF (International Floorball Federation) Certificate

FIVB Homologation Certificate

FIFA QUALITY PROGRAMME FOR FUTSAL SURFACES – FIFA Laboratory Test Report n. 114680

COLOR RANGE



VM11




VM82




VM10




VM18




VM21



VM90



VM70




VM41




VM23




VM81



VM30



VM66



VM67

INSTALLATION AND MAINTENANCE

The product must be stored and installed in appropriate conditions, including suitable protected premises at guaranteed minimum and maximum temperatures and humidity, as fully described in MONDO's *Storage and Installation Instructions*.

The product must be used and maintained following the premises described in MONDO's *Use and Maintenance Instructions*.

For additional product information, please refer to the Technical Data Sheet.